Model: C1400 D5

Frequency: 50
Fuel Type: Diesel

# » Generator set data sheet 1400kVA Standby @ 50Hz



# Our energy working for you.™

Spec sheet:	SS16-CPGK
Noise data sheet (Open/enclosed):	ND50-OSHHP/ND50-CSHHP
Airflow data sheet:	AF50-HHP
Derate data sheet (Open/enclosed):	DD50-OSHHP/DD50-CSHHP
Transient data sheet:	RTF

	Standby	Standby			Prime	Prime kVA (kW)		
Fuel consumption	kVA (kW	kVA (kW)		kVA (kV				
Ratings	1400 (11	20)			1250 (10	000)		
Load	1/4	1/2	3/4	Full	1/4	1/2	3/4	Full
gph	18.2	33.6	48.6	64.4	16.7	30.5	43.7	57.4
L/hr	83	153	221	293	76	139	199	261

Engine	Standby rating	Prime rating		
Engine manufacturer	Cummins	•		
Engine model	KTA50-G3			
Configuration	Cast Iron, 60° V16 Cylinde	er		
Aspiration	Turbo Charged and After-6	Cooled		
Gross engine power output, kWm	1228	1097		
BMEP at set rated load, kPa	1930.5	1730.6		
Bore, mm	159			
Stroke, mm	159	159		
Rated speed, rpm	1500	1500		
Piston speed, m/s	7.9	7.9		
Compression ratio	13.9:1			
Lube oil capacity, L	204			
Overspeed limit, rpm	1850 ±50	1850 ±50		
Regenerative power, kW	116	116		
Governor type	Electronic	Electronic		
Starting voltage	24V Volts DC			

Fue	flo	W	
i ac		**	

Maximum fuel flow, L/hr	624
Maximum fuel inlet restriction, mm Hg	203
Maximum fuel inlet temperature (°C)	70

# Air

Air		
Combustion air, m³/min	104.90	96.40
Maximum air cleaner restriction, kPa	6.2	



Exhaust	Standby rating	Prime rating
Exhaust gas flow at set rated load, m³/min	240.6	223.6
Exhaust gas temperature, C	525	520
Maximum exhaust back pressure, kPa	6.7	
Standard set-mounted radiator cooling		

<b>3</b>			
Ambient design, °C	40		
Fan load, KW <sub>m</sub>	46.3		
Coolant capacity (with radiator), L	345		
Cooling system air flow, m3/sec @ 12.7mmH2O	27.1		
Total heat rejection, BTU/min	44000 38500		
Maximum cooling air flow static restriction mmH2O	0.12		

# Open set derating factors kVA (kW)

Note: Standard open genset options running at 400V, 150m above sea level. For enclosed product derates, please refer to datasheet - DD50-CSHHP.

	27°C	40°C	45°C	50°C	55°C
Standby	1400 (1120)	1400 (1120)	1400 (1120)	1372.5 (1098)	RTF
Prime	1250 (1000)	1250 (1000)	1250 (1000)	1247.5 (998)	RTF


Weights*	Open	Enclosed
Unit dry weight kgs	9099	RTF
Unit wet weight kgs	10075	RTF

<sup>\*</sup> Weights represent a set with standard features. See outline drawing for weights of other configurations


Dimensions	Length	Width	Height
Standard open set dimensions	5105	2000	2238
Enclosed set standard dimensions	RTF	RTF	RTF

#### **Genset outline**

### Open set



### **Enclosed set**



Outlines are for illustrative purposes only. Please refer to the genset outline drawing for an exact representation of this model.



### **Alternator data**

Feature code	Connection <sup>1</sup>	Temp rise degrees C	Duty <sup>2</sup>	Alternator	Voltage
B667	Wye, 3 Phase	150/125	S/P	P7B	380-440V
•					

**Ratings definitions** 

Emergency Standby Power (ESP)	Limited-Time running Power	Prime Power (PRP):	Base Load (Continuous) Power
Applicable for supplying power to	Applicable for supplying power to a	Applicable for supplying power to	Applicable for supplying power
varying electrical load for the	constant electrical load for limited	varying electrical load for unlimited	continuously to a constant electrical
duration of power interruption of a	hours. Limited Time Running	hours. Prime Power (PRP) is in	load for unlimited hours.
reliable utility source. Emergency	Power (LTP) is in accordance with	accordance with ISO 8528. Ten	Continuous Power (COP) in
Standby Power (ESP) is in	ISO 8528.	percent overload capability is	accordance with ISO 8528, ISO
accordance with ISO 8528. Fuel		available in accordance with ISO	3046, AS 2789, DIN 6271 and BS
Stop power in accordance with ISO		3046, AS 2789, DIN 6271 and BS	5514.
3046, AS 2789, DIN 6271 and BS		5514.	
5514.			

### Formulas for calculating full load currents:

Three phase output Single phase output

kW x 1000 kW x Single Phase Factor x 1000

Voltage x 1.73 x 0.8 Voltage

#### See your distributor for more information.

Cummins Power Generation Manston Park, Columbus Avenue Manston, Ramsgate Kent CT12 5BF, UK Telephone: +44 (0) 1843 255000

Fax: +44 (0) 1843 255902 E-Mail: cpg.uk@cummins.com Web: www.cumminspower.com

